NON-BIDDING

PROPOSAL

TRANSPORTATION CABINET Department of Highways Frankfort, Kentucky 40622

	•
PROJECT CODE NO. 03-0049	LETTING OF JANUARY 17, 2003
- NOBECT CODE NO	Sealed Bids will be received in the Division of Contract Procurement
	and/or the Auditorium located on the
•	1st Floor of the State Office
	Building until 10:00 A.M., EST, on JANUARY 17, 2003. Bids will
	be publicly opened and read at 10:00
PROJECT IDENTIFICATION AND DESCRIPTION:	A.M., EASTERN STANDARD TIME.
WASHINGTON COUNTY, FD05 115 0390 000-002	
The Seaville-Harrodsburg Road (KY 390) from KY 53 (ME	P 0.000) extending easterly to the
Mercer County Line (MP 1.586), a distance of 1.586 mi	iles.
Asphalt Surface.	
(4)	
THE SUCCESSFUL BIDDER ON THIS PROJECT MAY REQUEST A W	WORK ORDER WITH AN EFFECTIVE DATE PRIOR
TO JUNE 15, 2003. THE REQUEST MUST BE IN WRITING TO	THE DEPARTMENT. A WORK ORDER ISSUED AT
THE REQUEST OF THE CONTRACTOR WILL BE WITH THE DISTIN WORK PERFORMED ESTIMATES MAY BE DELAYED UNTIL JULY 15	NCT UNDERSTANDING THAT PAYMENT FOR ANY
JUNE 15, 2003, FOR THIS PROJECT UNLESS THE BIDDER REQ	QUESTS AN EARLIER WORK DATE.
GEOGRAPHIC COORDINATES:	
LATITUDE - 37° 45' NORTH	
LONGITUDE - 85° 10' WEST	
COMPLETION DATE ESTABLISHED FOR PROJECT: OCTO	DBER 30, 2003
LIQUIDATED DAMAGES SEE	STANDARD SPECIFICATIONS
REQUIRED BID PROPOSAL GUARANTY: Not less than 5% of	the total bid.
(Check guaranty submitted: Cashier's Check	Certified Check Bid Bond)
BID BONDS WHEN SUBMITTED WILL BE RET	
PART INDEX OF CONTEN	ITS
I SCOPE OF WORK	
II SPECIAL PROVISIONS APPLICABLE TO PROJECT	
III EMPLOYMENT, WAGE AND RECORD REQUIREMENTS	
IV INSURANCE	
V STATEMENT OF INCOMPLETED WORK AND SUBCONT	RACTED WORK
VI BID ITEMS	
VII CERTIFICATION	
BID PROPOSAL ISSUED TO:	
CDECTMEN	

Address

City

Zip


State

PART I

SCOPE OF WORK

1		Project	Detail
---	--	---------	--------


a.	See Sketch and Typical Section	Attached
b.	Special Notes Applicable to Project	Attached
c.	Supplemental Specifications	Attached
d.	Special Note for Traffic Control Plan	Attached
e.	Special Note for Typical Section Dimensions	Attached
f.	Special Note for Award of Contract	Attached



TYPICAL SECTION

Washington County

FD05-115-0390-000-002



SPECIAL NOTES APPLICABLE TO PROJECT

THE FOLLOWING STANDARD DRAWINGS APPLY TO THIS PROJECT AND MAY BE OBTAINED BY CONTACTING THE DEPARTMENT OF HIGHWAYS, DIVISION OF DESIGN, AT A COST OF \$0.50 PER COPY:

Miscellaneous Standards Part 1 (RGX-001-04)
Approaches, Entrances, and Mail Box Turnout (RPM-110-04)
Lane Closure Two-Lane Highway Case II (TTC-105)
Miscellaneous Traffic Control Devices (TTD-100)
Miscellaneous Traffic Control Devices (TTD-105)
Post Splicing Detail (TTD-110)

2000 SPECIFICATIONS

Any reference in the plans or proposal to the Standard Specifications for Road and Bridge Construction, Edition of 1998, and Standard Drawings, Edition of 2000 are superseded by Standard Specifications for Road and Bridge Construction, Edition of 2000 and Standard Drawings, Edition of 2003.

2001 SUPPLEMENTAL SPECIFICATIONS

The **2001 Supplemental Specifications** to the 2000 Standard Specifications for Road and Bridge Construction shall apply to this project.

PROPOSAL ADDENDA

All Addenda to this proposal must be incorporated into the proposal when the bid is submitted to the Kentucky Department of Highways. Failure to use the correct and most recent bid sheet(s) may result in the bid being rejected.

BID SUBMITTAL

Bidder must use the Department's Highway Bid Program available on the internet web site of the Department of Highways, Division of Contract Procurement. (www.kytc.state.ky.us/contract)

The Bidder must download the bid items created from the web site to prepare a bid proposal for submission to the Department. The bidder must insert the completed bid item sheets printed from the Program into the bidder's proposal and submit with the disk created by said program.

JOINT VENTURE BIDDING

Joint Venture bidding is permissible. However, both companies <u>MUST</u> purchase a bidding proposal. Either proposal may be submitted but must contain the company names and signatures of both parties where required. A joint bid bond of 5% may be submitted for both companies or each company may submit a separate bond of 5%.

UNDERGROUND FACILITY DAMAGE PROTECTION

The contractor is advised that the Underground Facility Damage Protection Act of 1994, became law January 1, 1995. It is the contractor's responsibility to determine the impact of the act regarding this project, and take all steps necessary to be in compliance with the provisions of the act.

ASPHALT BASE PRICE

The Asphalt Base Price shall be \$170.00 (english) as applicable in Section 109.07 of the 2000 Standard Specifications.

INCIDENTAL SURFACING

The quantities established in the proposal include estimated quantities required for resurfacing or surfacing mailbox turnouts, farm field entrances, residential and commercial entrances, and road and street approaches. These items are to be paved to the limits as shown on Standard Drawing RPM 110 or to the limits as directed by the Engineer. In the event signal detectors are present in the intersecting streets or roads, the paving of the crossroads shall be to the right of way limit or back of the signal detector, whichever is the farthest back of the mainline. These areas are to be surfaced or resurfaced as directed by the Engineer and no direct payment will be allowed for placing and compacting.

SPECIAL NOTES APPLICABLE TO PROJECT (Continued)

OPTION B

The Contractor is advised that the compaction of asphalt mixtures furnished to this project will be accepted by OPTION B in accordance with Section 402 and Section 403 of the 2000 Standard Specification.

Mainline Surfacing Width 18 Feet.

Total area to be Surfaced 18423 Square Yards.

Class 1 Asphalt Surface 0.38D PG 64-22 estimate based on depth of 1" - 110 lbs/s.y.

The ADT for this project is estimated at 340.

SHOULDERS (2791 Sq. Yds.) 1.5' wide on each side.

DGA Base for Shoulders based on 115 lbs./Sq Yd per inch of depth.

Payment for necessary grading and/or shaping of existing shoulders prior to placing of DGA Base shall be included in the unit price bid per ton for DGA Base.

Supplemental Specifications to The Standard Specifications for Road and Bridge Construction, 2000 Edition

(Effective-with the October 25, 2002 Letting)

Unless stated o	therwise, all revisions are to the Standard Specifications for Road and Bridge Construction.
PUBLICATION:	2001 Supplemental Specifications to The Standard Specifications for Road and Bridge
	Construction.
SUBSECTION:	104.02.02 Overrun and Underrun Formulas.
REVISION:	Void the revision.
SUBSECTION:	104.02.02 Overrun and Underrun Formulas.
REVISION:	Replace the fifth paragraph with the following:
	For the excessive underrun and overrun quantities, the Department will adjust the payment
	according to the appropriate following formula:
SUBSECTION:	104.02.02 Overrun and Underrun Formulas.
NUMBER:	3)
REVISION:	Replace the threshold value of 20 percent with 30 percent.
SUBSECTION:	102.07.01 General.
REVISION:	Replace the first sentence with the following:
REVISION.	Replace the first sentence with the following.
	Submit the Bid Proposal on the forms furnished by the Department including the Highway Bid
CIDCECTION	Program bid item sheets and disk created from the Department's internet web site. 102.07.02 Computer Bidding.
SUBSECTION:	
REVISION:	Replace the subsection with the following:
	C. I
	Subsequent to ordering a Bid Proposal for a specific project, use the Department's Highway Bid
	Program on the internet web site of the Department of Highways, Division of Contract
	Procurement. Download the bid item quantities from the Department's web site to prepare a Bid
	Proposal for submission to the Department. Insert the completed bid item sheets printed from the
	Highway Bid Program into the Proposal and submit along with the disk created by said program.
·	In case of a dispute, the Bid Proposal and bid item sheets created by the Highway Bid Program
	take precedence over any bid submittal.
	Furthermore the Department takes no responsibility for loss, damage of disks or the
	compatibility with the bidder's computer equipment or software.
SUBSECTION:	102.08 IRREGULAR BID PROPOSALS.
REVISION:	Add the following to the first set of items:
	0 T I 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
	4) Fails to submit a disk created from the Highway Bid Program
SUBSECTION:	102.08 IRREGULAR BID PROPOSALS.
REVISION:	Replace 1) of the second set of items with the following:
	1) when the Bid Proposal is on a form other than that furnished by the Department or printed from
	other than the Highway Bid Program, or when the form is altered or any part is detached.
SUBSECTION:	112.03.01 General Traffic Control.
PART:	I) Temporary Traffic Signals.
REVISION:	Replace the MUTCD reference "Section 4B" with "Chapter 4D"
SUBSECTION:	212.03.03 Permanent Seeding and Protection.
PART:	A) Seed Mixtures for Permanent Seeding.
REVISION:	Replace with the following:
	A) Seed Mixture for Permanent Seeding. Use seed Mixture No. I or as the Contract specifies.
	Mixture No. I:
-	
*	75% Kentucky 31 Fescue (Festuca arundinacea)
	10% Red Top (Agrostis alba)
	5% White Dutch Clover (Trifolium repens)
	10% Rygrass, perennial (Lolium perenne)
L	

Supplemental Specifications to The Standard Specifications for Road and Bridge Construction, 2000 Edition

(Effective with the October 25, 2002 Letting)

SUBSECTION:	212.03.03 Permanent Seeding and Protection.
PART:	C) Crown Vetch.
REVISION:	Replace the first sentence with the following:
•	
	Sow crown vetch seed on all areas having a slope 3:1 or steeper and consisting of soil or mixtures
	of broken rock and soil.
SUBSECTION:	
PART:	,
REVISION:	Replace the first sentence with the following:
	T . 11
	Install erosion control blankets in ditches, except those to be paved or rock lined, to a flow depth of
armanantari	1.5 feet.
SUBSECTION:	402.03.02 Acceptance.
PART:	C) Setup.
REVISION:	Add the following after the second sentence:
	For mixtures with a total-project quantity between 500 and 1,000 tons, perform a minimum of one
	process control test for AC, AV, and VMA, and report the results to the Engineer.
SUBSECTION:	402.03.03 Verification.
REVISION:	Replace the first two sentences with the following:
KEVISION:	Replace the first two sentences with the following.
	For volumetric properties, the Department will perform a minimum of one verification test for AC,
	AV, and VMA for each lot according to the corresponding procedures as given in Subsection
	402.03.02. For specialty mixtures, the Department will perform one AC and one gradation
	determination per lot according to the corresponding procedures as given in Subsection 402.03.02.
	However, Department personnel will not perform AC determinations according to KM 64-405.
SUBSECTION:	403.02.06 Transport Equipment.
REVISION:	Add the following after the first sentence:
ALE VIBIO, III	The de the first the trace of t
	Do not load trucks that are contaminated with an unapproved release agent. When such
	contamination is identified after loading, reject the load. In either case, remove the truck and
	respective driver from the project for the duration of the project.
SUBSECTION:	403.03.03 Preparation of Mixture.
PART:	A) Mixture Composition.
REVISION:	Replace the second sentence with the following:
	Conform to the gradation requirements (control points) of AASHTO MP2 for the Superpave mixture
	type the Contract specifies.
SUBSECTION:	403.03.03 Preparation of Mixture.
PART:	C) Mix Design Criteria.
REVISION:	Replace the first sentence with the following:
,	G. C. A. A. C. Control maints) of AACUTO MP2 for the Superpaye
	Conform to the gradation requirements (control points) of AASHTO MP2 for the Superpave
ormon composition	mixture.
SUBSECTION:	403.03.03 Preparation of Mixture.
PART:	C) Mix Design Criteria.
NUMBER:	2) Selection of Optimum AC.
REVISION:	Add the following:
	Ensure the optimum AC is a minimum of 5.0 percent by weight of the total mixture for all 0.5-inch
	nominal surface mixtures and 5.3 percent by weight of the total mixture for all 0.38-inch nominal
	surface mixtures.
SECTION:	403.03.06 Thickness Tolerance.
TABLE:	Nominal Maximum Size of Mixture vs. Thickness Range
REVISION:	Delete
VEATOROIA:	Delete

Supplemental Specifications to The Standard Specifications for Road and Bridge Construction, 2000 Edition

(Effective with the October 25, 2002 Letting)

SUBSECTION: 403.03.09 Leveling and Wedging, and Scratch Course.

PART:

A) Leveling and Wedging.

REVISION:

Replace the first sentence with the following:

Conform to the gradation requirements (control points) for base, binder, or surface as applicable.

SUBSECTION:

403.03.09 Leveling and Wedging, and Scratch Course.

PART:

B) Scratch Course.

REVISION:

Replace the second sentence with the following:

Conform to the gradation requirements (control points) for base, binder, or surface as the Engineer

directs.

SECTION:

404 OPEN-GRADED FRICTION COURSE

TABLE:

LOT PAY ADJUSTMENT SCHEDULE FOR SPECIALTY MIXTURES

REVISION:

Replace the table with the table on the last page of this supplement.

SUBSECTION: **REVISION:**

409.02 MATERIALS AND EQUIPMENT. Replace "KM 64-427" with the following:

the guidelines in Subsection 409.03.02

SUBSECTION:

409.03.01 Restrictions.

REVISION:

Add the following sentence:

When the mixture's bid item specifies PG 76-22, limit RAP content to 20 percent or less. 2001 Supplemental Specifications to The Standard Specifications for Road and Bridge Construction.

PUBLICATION:

409.03.02 Preparation of Mixture.

SUBSECTION:

A) Mix Requirements.

PART: REVISION:

Void the Revision and replace with the following:

Conform to the Contract requirements for each mixture produced using RAP. If mixtures produced using RAP do not conform to the requirements for that mixture, complete the project using all virgin materials at no additional expense to the Department. Conform to the following table to select the appropriate grade of virgin asphalt binder to blend with the RAP:

Mixture's	Appropriate Virgin Asphalt Binder						
Bid Item	0-20% RAP	• • • • • • • • • • • • • • • • • • • 					
PG 76-22	PG 76-22	-	-				
PG 70-22	PG 70-22	PG 64-22	*				
PG 64-22	PG 64-22	PG 64-22	* .				

^{*} Select according to KM 64-427

SUBSECTION:

611.03.02 Precast Unit Construction.

REVISION:

Replace the first sentence with the following:

Construct units according to ASTM C 1433 with the following exceptions and additions:

PUBLICATION:

2001 Supplemental Specifications to The Standard Specifications for Road and Bridge Construction.

SUBSECTION:

701.03.05 Joints.

PART:

B) Corrugated Metal Pipe.

REVISION:

Void the Revision and replace with the following:

Construct joints using a band with annular corrugations and a bolt, bar and strap connection. Use a minimum nominal band width of 12 inches for all pipe diameters 54 inches and smaller. Use a twopiece band with a minimum nominal width of 20 inches for all pipe diameters greater than 54 inches. Manufacture the band from the same base materials as the pipe. The pipe bands may be up to two gauges lighter than the pipe it is joining, with a minimum gauge thickness of 16. The Department may allow dimple band connections for field cut pipe. Install the connecting bands according to the manufacturer's written recommendations.

Supplemental Specifications to The Standard Specifications for Road and Bridge Construction, 2000 Edition (Effective with the October 25, 2002 Letting)

SUBSECTION:	710.02 MATERIALS.
REVISION:	Add the following Subsection:
	TARREST AND THE RELATION AND A STATE OF THE
	710.02.15 High Density Polyethylene (HDPE) Adjusting Rings. Conform to Section 846.
SUBSECTION:	710.03.01 Newly Constructed Small Drainage Structures.
PART:	A) General.
REVISION:	Replace the last sentence of the sixth paragraph with the following:
	TOO
	Use precast concrete, precast concrete pipe sections, cast-in-place, brick, or HDPE adjusting rings
	for adjustment of existing manholes according to the Standard Specifications.
SUBSECTION:	710.03.03 Adjusted Small Drainage Structures.
REVISION:	Add the following sentence to the end of the first paragraph:
	For HDPE adjusting rings, install and seal according to the manufacturer's recommendations.
CEDCE CETON.	713.03 CONSTRUCTION.
SUBSECTION:	Replace the MUTCD references to "Part III" with "Part 3"
REVISION:	
SUBSECTION:	714.03 CONSTRUCTION. Replace the MUTCD references to "Part III" with "Part 3" and figure references to "3-11 and 3-12"
REVISION:	
CTITION CHILON	with "3B-8 and 3B-9"
SUBSECTION:	714.03.01 Layout.
REVISION:	Replace the MUTCD reference to "Part III" with "Part 3"
PUBLICATION:	2001 Supplemental Specifications to The Standard Specifications for Road and Bridge Construction.
SUBSECTION:	714.05 PAYMENT.
REVISION:	Replace with the following:
	The Department will make payment upon completion of the work. If after the proving period the
	markings do not meet minimum retroreflectivity requirements, the Department will adjust the
	payment or require corrective work according to the following:
SUBSECTION:	718.01 DESCRIPTION.
REVISION:	Replace the second sentence with the following:
REVISION.	replace the second sentence with the rono wing.
	See Section 3C.01 of the MUTCD for a general description.
SUBSECTION:	807.02.03 Joint Sealer for Ridged Pipe.
PART:	B) Rubber Gaskets.
REVISION:	Replace with the following:
	B) Butyl Rubber Sealants. Furnish butyl rubber sealants conforming to the materials, manufacture,
	and physical requirements for sealants in AASHTO M 198, Section 6.2. Use only products from
	the Department's List of Approved Materials.
SUBSECTION:	807.02.03 Joint Sealer for Ridged Pipe.
PART:	C) Flexible Plastic Gaskets.
REVISION:	Replace with the following:
	a
· .	C) Rubber Gaskets. Furnish rubber gaskets conforming to the materials, manufacture, and physical
*	requirements for gaskets in AASHTO M 315. Use only products from the Department's List of
	Approved Materials.

Supplemental Specifications to The Standard Specifications for Road and Bridge Construction, 2000 Edition

(Effective with the October 25, 2002 Letting)

846 HIGH DENSITY POLYETHYLENE (HDP	PE) ADJUSTING RINGS			
Add the following New Section:				
CROWN AND THE PRINCIPLE POLYMPTING THE AMBREL A BRICARIO BRICA				
· SECTION 846 HIGH DENSITY POLYETHYLI	ENE (HDPE) ADJUSTING KINGS			
846.01 RESIN. Use a recycled polyethylene meeting the following requirements:	e plastic or virgin resin producing a molded part			
Melt Flow Index (ASTM D 1238) 4.	.0-10.0 g/10min			
	.941-0.965 g/cm ³ 000-5000 lb/in ²			
	ondition C			
ESCR (ASIM D 1093)	ondraon C			
846.02 LOADING. Ensure the adjustment r	ings meet or exceed the loading requirements of heel loading for Highway Bridges.			
Replace with the following:	. •			
Provisions for Seed Certification in Kentucky" and	quirements outlined in the "Kentucky Seed Law and d the "Regulations under the Kentucky Seed Law",			
with following exceptions.				
1. Obtain seed only through registered dealer	ers that are permitted for labeling of seed.			
4. Insuic an bags and containers have an ac	soopmoto good tag atmonota			
germination (including hard seed) is less than 60%	nd legumes) if the weed seed is over 2%, total, if the seed test date is over 9 months old exclusive			
of the month tested, or if the limits of noxious wee	d seed is exceeded.			
Ensure that noxious weed seeds contained	in any seed or seed mixture does not exceed the			
maximum permitted rate of occurrence per pound.				
	Max. No. Seeds			
	(per pound)*			
Balloon Vine (Cardiospermum Halicacabum)	0			
Purple Moonflower (Ipomoea turbinata)	0			
Canada Thistle (Cirsium Arvense)	U Almum and perennial rhizomatous derivatives of			
	Amum and percinnal inizoliatous desiratives of			
	0			
	256			
	304			
	192			
	192			
	192			
Orace Dairy (Chrisanthemum Jeucanthemum)	256			
	256			
Correl / Rumey A cetosella l				
Sorrel (Rumex Acetosella) Wild Onion and Wild Garlic (Allium spp.)	96			
	Add the following New Section: SECTION 846 HIGH DENSITY POLYETHYLE 846.01 RESIN. Use a recycled polyethylene meeting the following requirements: Melt Flow Index (ASTM D 1238) 4 Density (ASTM D 792) 0. Tensile (ASTM D 638) 20 ESCR (ASTM D 1693) CO 846.02 LOADING. Ensure the adjustment of AASHTO'S Standard Specification for HS-25 with the following: 827.04 PERMANENT SEED. Conform to the receptor with the following: 827.04 PERMANENT SEED. Conform to the receptor with following exceptions: 1. Obtain seed only through registered dealers. Ensure all deliveries/shipments of preming the Department may sample the seed at the Ensure all bags and containers have an account of the month tested, or if the limits of noxious were seed of the month tested, or if the limits of noxious were seed of the month tested, or if the limits of noxious were			

Wildflower seed shall not be planted until approved by the MCL.

Supplemental Specifications to The Standard Specifications for Road and Bridge Construction, 2000 Edition (Effective with the October 25, 2002 Letting)

LOT PAY ADJUSTMENT SCHEDULE FOR SPECIALTY MIXTURES (TEST DEVIATION FROM JMF)				
	Pay Value	Deviation From JMF (%)		
Asphalt	1.00	0.0-0.5		
Binder	0.98	0.6		
Content	0.95			
Contait	0.90	0.7		
	0.85	0.8		
	0.75	≥ 0.9		
1 1/2 inch	1.00	0-13		
1	0.98	14		
Sieve	0.95	15-16		
		17-20		
	0.90	21-23		
	0.85			
	0.75	≥24		
l inch,	1.00	0-9		
3/4 inch,	0.98	10		
and 1/2 inch	0.95	11-12		
Sieves	0.90	13-14		
	0.85	15-16		
-	0.75	≥ 17		
3/8 inch,	1.00	0-8		
No. 4,	0.98	. 9		
No. 8,	0.95	10		
No. 16,	0.90	11-12		
and No. 30	0.85	13-14		
Sieves	0.75	≥ 15		
No. 50	1.00	0-6		
Sieve	0.98	7		
Sieve	0.95	8		
	0.90	9		
	0.85	10		
	0.75	≥11		
No. 100	1.00	0-3		
Sieve	0.98			
Piece	0.95	4		
	0.90	5		
	0.85			
	0.83	≥6		
37 000		0.0-2.0		
No. 200	1.00	2.5		
Sieve	0.98	3.0		
	0.95	3.0		
	0.90	3.5		
j	0.85	1		
	0.75	≥ 4.0		
Fineness	1.00	0.0-0.30		
Modulus	0.98	0.31-0.34		
	0.95	0.35-0.39		
	0.90	0.40-0.46		
	0.85	0.47-0.55		
1	0.75	≥ 0.56		

TRAFFIC CONTROL PLAN FD05-115-0390-000-002

TRAFFIC CONTROL GENERAL

Except as provided herein, traffic shall be maintained in accordance with the 2000 Standard Specifications and the Standard Drawings, current editions. Except for the roadway and traffic control bid items listed, all items of work necessary to maintain and control traffic will be paid at the lump sum bid price to "Maintain and Control Traffic".

Contrary to Section 106.01, traffic control devices used on this project may be new, or used in like new condition, at the beginning of the work and maintained in like new condition until completion of the work.

PROJECT PHASING & CONSTRUCTION PROCEDURES

At the discretion of the Engineer, days and hours may be specified when lane closures will not be allowed.

The Contractor may maintain alternating one way traffic during construction. The clear lane width shall be 9 feet. If traffic should be stopped due to construction operations, and a school bus on an official run arrives on the scene, the Contractor shall make provisions for the passage of the bus as quickly as possible.

LANE CLOSURES

Do not leave lane closures in place during non-working hours.

SIGNS

Contrary to Section 112.04.02 and 112.04.03, Low Shoulder signs will not be measured for payment, but will be incidental to Maintain and Control Traffic. Contrary to section 112.04.02, only long term signs (signs intended to be continuously in place for more than 3 days) will be measured for payment; short term signs (signs intended to be left in place for 3 days or less) will not be measured for payment but will be incidental to Maintain and Control Traffic.

Traffic Control Plan FD05-115-0390-000-002 Page 2

BARRICADES

Barricades used in lieu of barrels and cones for channelization or delineation will be incidental to Maintain and Control Traffic according to Section 112.04.01. Barricades used to protect pavement removal areas will be bid as each according to Section 112.04.05.

PAVEMENT EDGE DROP-OFFS

A pavement edge between opposing directions of traffic or lanes that traffic is expected to cross in a lane change situation shall not have an elevation difference greater than 1½". Warning signs (MUTCD W8-11 or W8-9A) shall be placed in advance of and at 1500 feet intervals throughout the drop-off area. Dual posting on both sides of the traveled way shall be required. All transverse transitions between resurfaced and unresurfaced areas which traffic may cross shall be wedged with asphalt mixture for leveling and wedging. The wedges shall be removed prior to placement of the final surface course.

Pavement edges that traffic is not expected to cross, except accidentally, shall be treated as follows:

Less than 2" - No protection required.

2" to 4" - Place plastic drums, vertical panels, or barricades every 50 feet. Cones may be used in place of plastic drums, panels, and barricades during daylight working hours. Wedge with asphalt mixture for leveling and wedging with a 1:1 or flatter slope in daylight hours, or 3:1 or flatter slope during nighttime hours, when work is not active in the drop-off area.

2lane.TCP 8/16/2002

SPECIAL NOTE FOR TYPICAL SECTION DIMENSIONS

FD05-115-0390-000-002

The dimensions shown on the typical sections for pavement and shoulder widths and thicknesses are nominal or typical dimensions. The actual dimensions to be constructed may be varied to fit existing conditions as directed or approved by the Engineer. It is not intended that existing pavement or shoulders be widened unless specified elsewhere in the Proposal.

Typical Section 7/11/2002

SPECIAL NOTE FOR AWARD OF CONTRACT FD05 115-0390-000-002

Contrary to Section 103.02, the Department may hold the Bid Proposals of any or all bidders for a period not to exceed 90 calendar days for final disposition of award. The Department may hold the Bid Proposal of the lowest bidder longer than 90 calendar days if the bidder concurs.

Contrary to Section 103.04, The Department will hold the Proposal Guaranty of the lowest bidder and the Proposal Guaranty of the second lowest bidder, as determined by the Commissioner, until the Department awards the Contract and executes and approves the Contract and bond of the successful bidder, or until the Department rejects all Bid Proposals. If the Department does not make an award within 90 calendar days, the Department will return all Proposal Guaranties.

Except as provided in this note or elsewhere in the proposal, all other applicable portions of Section 103 apply.

PART II

SPECIAL PROVISIONS APPLICABLE TO PROJECT

SPECIAL PROVISION NO.

TITLE

NO SPECIAL PROVISIONS APPLY TO THIS PROJECT

PART III

EMPLOYMENT, WAGE AND RECORD REQUIREMENTS (Copies of each Attached)

- 1. Schedule of Minimum Wages Established for the Project.
- 2. Labor and Wage Requirements, applicable to other than Federal-Aid System Contracts. (Rev. 2-16-95)
- 3. Executive Branch Code of Ethics.

TRANSPORTATION CABINET DIVISION OF CONTRACT PROCUREMENT COMPLIANCE SECTION

PROJECT WAGE RATES

LETTING: 01-17-2003

WASHINGTON COUNTY, FD05 115 0390 000-002

The Seaville-Harrodsburg Road (KY 390) Asphalt Surface

CONSTRUCTION WORKERS MINIMUM HOURLY RATE . . . \$5.15

Note: Parts III and IV of "Labor and Wage Requirements Applicable To Other Than Federal-Aid System Projects" do not apply to this project.

TRANSPORTATION CABINET DEPARTMENT OF HIGHWAYS

LABOR AND WAGE REQUIREMENTS APPLICABLE TO OTHER THAN FEDERAL-AID SYSTEM PROJECTS

Application

I. II. Nondiscrimination of Employees (KRS 344) Ш. Payment of Predetermined Minimum Wages

Statements and Payrolls IV.

I. APPLICATION

1. These contract provisions shall apply to all work performed on the contract by the contractor with his own organization and with the assistance of workmen under his immediate superintendence and to workmen under his immediate superintendence and to all work performed on the contract by piecework, station work or by subcontract. The contractor's organization shall be construed to include only workmen employed and paid directly by the contractor and equipment owned or rented by him, with or without operators.

2. The contractor shall insert in each of his subcontracts all of the stimulations contained in these

subcontracts all of the stipulations contained in these Required Provisions and such other stipulations as may

be required.

3. A breach of any of the stipulations contained in these Required Provisions may be grounds for termination of the contract.

II. NONDISCRIMINATION OF EMPLOYEES

AN ACT OF THE KENTUCKY GENERAL ASSEMBLY TO PREVENT DISCRIMINATION IN EMPLOYMENT KRS CHAPTER 344 EFFECTIVE JUNE 16, 1972

The contract on this project, in accordance with KRS Chapter 344, provides that during the performance of this contract, the contractor agrees as follows:

The contractor shall not fail or refuse to hire, or shall not discharge any individual, or otherwise discriminate against an individual with respect to his compensation, terms, conditions, or privileges of employment, because of such individual's race, color, employment, because of such individual's race, color, religion, national origin, sex, disability or age (between forty and seventy); or limit, segregate, or classify his employees in any way which would deprive or tend to deprive an individual of employment opportunities or otherwise adversely affect his status as an employee, because of such individual's race, color, religion, national origin, sex, disability or age (between forty and seventy). The contractor agrees to post in conspicuous places, available to employees and applicants for employment notices to be provided setting forth the

places, available to employees and applicants for employment, notices to be provided setting forth the provisions of this nondiscrimination clause.

2. The contractor shall not print or publish or cause to be printed or published a notice or advertisement relating to employment by such an employer or membership in or any classification or referral for employment by the employment agency, indicating any preference, limitation, specification, or discrimination, based on race, color, religion, national origin, sex, disability or age (between forty and seventy), except that such notice or advertisement may indicate a preference, limitation, or specification based indicate a preference, limitation, or specification based on religion, or national origin when religion, or national origin is a bona fide occupational qualification for

employment.

3. If the contractor is in control of apprenticeship or other training or retraining, including on-the-job training programs, he shall not discriminate against an individual because of his race, color, religion, national origin, sex, disability or age (between forty and seventy), in admission to, or employment in

any program established to provide apprenticeship or

other training.

4. The contractor will send to each labor union or representative of workers with which he has a collective bargaining agreement or other contract or understanding, a notice to be provided advising the said labor union or workers' representative of the contractor's commitments under this section, and shall post copies of the notice in conspicuous places available to employees and applicants for employment. The contractor will take such action with respect to any subcontract or purchase order as the administrating agency may direct as a means of enforcing such provisions, including sanctions for non-compliance.

PAYMENT OF PREDETERMINED III. MINIMUM WAGES

1. These special provisions are supplemented elsewhere in the contract by special provisions which set forth certain predetermined minimum wage rates. The contractor shall pay not less than those rates.

2. The minimum wage determination schedule shall be posted by the contractor, in a manner prescribed by the Department of Highways, at the site of the work in prominent places where it can be easily

seen by the workers.

IV. STATEMENTS AND PAYROLLS

1. All contractors and subcontractors affected by the terms of KRS 337.505 to 337.550 shall keep full and accurate payroll records covering all disbursements of wages to their employees to whom they are required to pay not less than the prevailing rate of wages. Payrolls and basic records relating thereto will be maintained during the course of the work and preserved for a period of one (1) year from the date of completion of this contract.

2. The payroll records shall contain the name, address and social security number of each employee, his correct classification, rate of pay, daily and weekly number of hours worked, itemized deductions made and

actual wages paid.

3. The contractor shall make his daily records available at the project site for inspection by the State Department of Highways contracting office or his

authorized representative.

Periodic investigations shall be conducted as required to assure compliance with the labor provisions of the contract. Interrogation of employees and officials of the contractor shall be permitted during working hours.

working hours.

Aggrieved workers, Highway Managers,
Assistant District Engineers, Resident Engineers and
Project Engineers shall report all complaints and
violations to the Division of Contract Procurement.

The contractor shall be notified in writing of
apparent violations. The contractor may correct the
reported violations and notify the Department of
Highways of the action taken or may request an
informal hearing. The request for hearing shall be in
writing within ten (10) days after receipt of the notice of
the reported violation. The contractor may submit
records and information which will aid in determining
the true facts relating to the reported violations. the true facts relating to the reported violations

Any person or organization aggrieved by the action taken or the findings established as a result of an informal hearing by the Division of Contract Procurement may request a formal hearing.

4. The wages of labor shall be paid in legal tender of the United States, except that this condition will be considered satisfied if payment is made by a negotiable check, on a solvent bank, which may be cashed readily by the employee in the local community for the full amount, without discount or collection charges of any kind. Where checks are used for payments, the contractor shall make all necessary arrangements for them to be cashed and shall give information regarding such arrangements.

information regarding such arrangements.

5. No fee of any kind shall be asked or accepted by the contractor or any of his agents from any person as a condition of employment on the project.

6. No laborers shall be charged for any tools used in performing their respective duties except for reasonably avoidable loss or damage thereto.

7. Every employee on the work covered by this contract shall be permitted to lodge, board, and trade where and with whom he elects and neither the contractor nor his agents, nor his employees shall directly or indirectly require as a condition of employment that an employee shall lodge, board or

trade at a particular place or with a particular person.
8. Every employee on the project covered by this contract shall be an employee of either the prime

contractor or an approved subcontractor.

9. No charge shall be made for any transportation furnished by the contractor or his agents

to any person employed on the work.

10. No individual shall be employed as a laborer or mechanic on this contract except on a wage basis, but this shall not be construed to prohibit the rental of teams, trucks or other equipment from individuals.

No Covered employee may be employed on the walk to be construed.

the work except in accordance with the classification set forth in the schedule mentioned above; provided, however, that in the event additional classifications are required, application shall be made by the contractor to the Department of Highways and (1) the Department shall request appropriate classifications and rates from the proper agency, or (2) if there is urgent need for additional classification to avoid undue delay in the work, the contractor may employ such workmen at rates deemed comparable to rates established for similar classifications provided he has made written application through the Department of Highways, addressed to the proper agency, for the supplemental rates. The contractor shall retroactively adjust, upon receipt of the supplemental rates schedule, the wages of any employee supplemental rates schedule. paid less than the established rate and may adjust the

wages of any employee overpaid.

11. No contractor or subcontractor contracting for any part of the contract work which may require or involve the employment of laborers or mechanics shall require or permit any laborer or mechanic in any work-week in which he is employed on such work, to work in excess of eight hours in any calendar day or in excess of forty hours in such work-week unless such laborer or mechanic receives compensation at a rate not less than one and one half times his basic rate of pay for all hours worked in excess of eight hours in any calendar day or in excess of forty hours in such work-week. A laborer, in excess of forty hours in such work-week. A laborer, workman or mechanic and an employer may enter into a written agreement or a collective bargaining agreement to work more than eight (8) hours a calendar day but not more than ten (10) hours a calendar day for the straight time hourly rate. This agreement shall be in writing and shall be executed prior to the employee working in excess of eight (8) hours, but not more than ten (10) hours, in any one (1) calendar day.

12. Payments to the contractor may be suspended or withheld due to failure of the contractor

to pay any laborer or mechanic employed or working on the site of the work, all or part of the wages required under the terms of the contract. The Department may suspend or withhold payments only after the contractor has been given written notice of the alleged violation and the contractor has failed to comply with the wage determination of the Department of Highways

13. Contractors and subcontractors shall comply with the sections of Kentucky Revised Statutes, Chapter

337 relating to contracts for Public Works.

Revised 2-16-95

EXECUTIVE BRANCH CODE OF ETHICS

In the 1992 regular legislative session, the General Assembly passed and Governor Brereton Jones signed Senate Bill 63 (codified as KRS 11A), the Executive Branch Code of Ethics, which states, in part:

KRS 11A.040 (6) provides:

No present or former public servant shall, within six (6) months of following termination of his office or employment, accept employment, compensation or other economic benefit from any person or business that contracts or does business with the state in matters in which he was directly involved during his tenure. This provision shall not prohibit an individual from returning to the same business, firm, occupation, or profession in which he was involved prior to taking office or beginning his term of employment, provided that, for a period of six (6) months, he personally refrains from working on any matter in which he was directly involved in state government. This subsection shall not prohibit the performance of ministerial functions, including, but not limited to, filing tax returns, filing applications for permits or licenses, or filing incorporation papers.

KRS 11A.040 (8) states:

A former public servant shall not represent a person in a matter before a state agency in which the former public servant was directly involved, for a period of one (1) year after the latter of:

- a) The date of leaving office or termination of employment; or
- b) The date the term of office expires to which the public servant was elected.

This law is intended to promote public confidence in the integrity of state government and to declare as public policy the idea that state employees should view their work as a public trust and not as a way to obtain private benefits.

If you have worked for the executive branch of state government within the past six months, you may be subject to the law's prohibitions. The law's applicability may be different if you hold elected office or are contemplating representation of another before a state agency.

Also, if you are affiliated with a firm which does business with the state and which employs former state executive-branch employees, you should be aware that the law may apply to them.

In case of doubt, the law permits you to request an advisory opinion from the Executive Branch Ethics Commission, Room 136, Capitol Building, 700 Capitol Avenue, Frankfort, Kentucky 40601; telephone (502) 564-7954.

PART IV

INSURANCE

The Contractor shall carry the following insurance in addition to the insurance required by law:

- (1) Contractor's Public Liability Insurance not less than \$100,000.00 for damages arising out of bodily injuries to or death to one person. Not less than \$300,000.00 for damages arising out of bodily injuries to or death to two or more persons.
- (2) Contractor's Property Damages Liability Insurance. Not less than \$100,000.00 for all damages arising out of injury or destruction of property in any one accident. Not less than \$300,000.00 for all damages during the policy period.
- (3) Contractor's Protective Public Liability and Property Damage Insurance. The contractor shall furnish evidence with respect to operations performed for him by subcontractors that he carries in his own behalf for the above stipulated amounts.
- (4) The insurance required above must be evidenced by a Certificate of Insurance and this Certificate of Insurance must contain one of the following statements:
 - a. "policy contains no deductible clauses."
- (5) WORKMEN'S COMPENSATION INSURANCE. The contractor shall furnish evidence of coverage of all his employees or give evidence of self-insurance by submitting a copy of a certificate issued by the Workmen's Compensation Board.

PART V

STATEMENT OF INCOMPLETED WORK

1. Status of Active Prime Contracts.

Attached

1. STATUS OF ALL INCOMPLETED PRIME CONTRACTS

All active prime contracts must be reported. This includes prime contracts with public and private owners and joint-ventured contracts. The names of the joint venturers must be shown when reporting these projects. A machine or typed listing reporting the status of each contract is acceptable when attached to this report; however, the total amounts on the itemized listing must be reported in the space provided below:

CONTRACT WITH	PROJECT IDENTIFICATION	PRIME CONTRACT AMOUNT	EARNINGS THROUGH LAST APPROVED ESTIMATE	TOTAL AMOUNT OF WORK REMAINING
	.			
				,
		<u></u>		
	<i>j</i>			
		4,,,,,,		
TOTAL (Attach Summary if not itemized above)		\$	\$	\$

PART VI

BID ITEMS

TRANSPORTATION CABINET

Department of Highways FRANKFORT, KY 40622

Sheet No:

1

WASHINGTON COUNTY FD05 115 0390 000-002

PCN: 03-0049

Letting: 1/17/2003

THE BIDDER MUST MAKE THE EXTENSIONS AND ADDITIONS SHOWING TOTAL AMOUNT BID USING FIGURES ONLY

Item No.	Code No.	Item	Approximate Quantity	 Unit	 	Unit Price Dollars		mount ollars
1	0001	D G A BASE	245.00	TON				
2	0190	LEVELING AND WEDGING PG64-22	210.00	TON		######################################		
3	0300	CL1 ASPH SURF 0.38D PG64-22	1,015.00	TON		B		
4	6514	PAVE STRIPING-PERM PAINT-4 IN	15,100.00	LIN FT				
5	6510	PAVE STRIPING-TEMP PAINT-4 IN	4,600.00	LIN FT				
6	2562	SIGNS	170.00	SQ FT		•		
7	2650	MAINTAIN AND CONTROL TRAFFIC	1.00	LP SUM		•		
8	2569	DEMOBILIZATION	1.00	LP SUM				•
9	I	TOTAL BID			<u> </u>		\$	

PART VII

CERTIFICATIONS

1.	Provisions Relative to Senate Bill 258 (1994)	Attached
2.	Non-Collusion Certification	Attached
3.	Certification of Bid Proposal	Attached

PROVISIONS RELATIVE TO SENATE BILL 258 (1994)

During provisi	the per	formance of	the contract, the contractor agrees to comply with applicable						
	1.	KRS 136	Corporation and Utility Taxes						
	2.	KRS 139	Sale and Use Taxes						
	3.	KRS 141	Income Taxes						
	4.	KRS 337	Wages and Hours						
	5.	KRS 338	Occupational Safety and Health of Employees						
	6.	KRS 341	Unemployment Compensation						
	7.	KRS 342	Workers Compensation						
Any final determinations of a violation by the contractor within the previous five (5) years pursuant to the applicable statutes above are revealed as follows:									
			. •						

NON-COLLUSION CERTIFICATION

COMMONWEALTH OF KENTUCKY COUNTY	
PROJECT NO.	
I, (Name of officer signing certificatio	n) (Title) , under
penalty of perjury under the laws of the United	States, do hereby certify that
(Insert name of Individual, Joint Venture, Co-pa	rtnership, or Corporation submitting bid)
its agent, officers or employees have not direct	ly or indirectly entered into any
agreement, participated in any collusion, or oth	erwise taken action in restraint of free
competitive bidding in connection with this prop	leso.
competitive brading in connection with this prop	JSGI.
	(Signature)
	(Title)
REVISED: 8-23-89	
NON-COLLUSION CER	TIFICATION
COMMONWEALTH OF KENTUCKY	
PROJECT NO.	
PRODECT NO.	
I,(Name of officer signing certification	, under
(Name of Officer signing certification	n) (Title)
penalty or perjury under the laws of the United :	States, do hereby certify that
(Insert name of Individual, Joint Venture, Co-pa	rtnership, or Corporation submitting bid)
ita amant affinana an amalanana bana mat dinant	les en imiliarent les entreuei interne
its agent, officers or employees have not direct	ly or indirectly entered into any
agreement, participated in any collusion, or other	erwise taken action in restraint of free
competitive bidding in connection with this propo	nga]
competitive starting in connection with this prope	
	(Girmahana)
	(Signature)
	(Title)
	(TTELA)

REVISED: 8-23-89

CERTIFICATION OF BID PROPOSAL

- We (I) propose to furnish all labor, equipment and materials necessary to construct and/or improve the subject project in accordance with the plans, the Transportation Cabinet's Standard Specifications for Road and Bridge Construction, current edition, special provisions, notes applicable to the project as indicated herein and all addenda issued on this project subsequent to purchase of proposal.
- We (I) attach a bid proposal guaranty as provided in the special provisions in an amount not less than 5% of the total bid. We agree to execute a contract in accordance with this bid proposal within 15 calendar days after the receipt of the notice of award for the project.
- We (I) have examined the site of proposed work, project plans, specifications, special provisions, and notes applicable to the project referred to herein. We understand that the quantities shown herein are estimated quantities subject to increase or decrease as provided in the specifications.

	,	Name of Contr	cacting Firm		
			3		
BY:					
Authorize	d Agent			Title	
	•				
Address		City	State	Zip Code	
		_		<u>-</u>	
Telephone Number					

When two or more organizations bid as a joint venture, enter names of each organization and an authorized agent for each organization must sign above.